


Comb  
A1  
variation in capacitance value of said first variable  
capacitance means by the first control voltage and in response  
to the variation in capacitance value of said second variable  
capacitance means by the second control voltage.

---

REMARKS

Claims 4-7 have been amended to remove multiple  
dependencies. Examination is respectfully requested.

Respectfully submitted,

  
John R. Mattingly  
Registration No. 30,293  
Attorney for Applicants

MATTINGLY, STANGER & MALUR  
1800 Diagonal Rd., Suite 370  
Alexandria, Virginia 22314  
(703) 684-1120  
Date: March 4, 2002

## MARKED UP VERSION OF REWRITTEN CLAIMS

4. (Amended) A modulation semiconductor integrated circuit device according to [any of] claim 1 [through claim 3], wherein said circuit of producing the second control voltage includes a digital filter which samples a digital transmission data signal and implements a computation for the sampled signal, and a D/A conversion circuit which implements the D/A conversion for the output of said digital filter, said controlled reference current value being the reference current value of said D/A conversion circuit.

5. (Amended) A modulation semiconductor integrated circuit device according to [any of] claim 1 [through claim 4], wherein said phase-locked loop includes a variable counter circuit which counts the oscillation output of said oscillation circuit, and a register which sets a value to be counted by said variable counter circuit, the base frequency being changed in response to the alteration of the value set in said register, the reference current value being controlled in accordance with the value set in said register.

6. (Amended) A modulation semiconductor integrated circuit device according to [any of] claim 1 [through claim 5] including a trimming circuit which adjusts the reference current value.

7. (Amended) A modulation semiconductor integrated circuit device according to [any of] claim 1 [through claim 6], wherein said voltage-controlled oscillation circuit includes a first variable capacitance means and a second variable capacitance means, and has its oscillation frequency varied in response to the variation in capacitance value of said first variable capacitance means by the first control voltage and in response to the variation in capacitance value of said second variable capacitance means by the second control voltage.